

Material Type	Size Dimensions	Non-reinforced	Reinforced	Roll Length	Roll Weight
STANDARD 0°F to +150°F					
FLAT	6" x 0.040"	X		500 feet	62 lbs.
	6" x 0.060"	X		400 feet	75 lbs.
	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.080"	X		300 feet	150 lbs.
	12" x 0.120"	X		200 feet	150 lbs.
	16" x 0.160"	X	X	150 feet	200 lbs.
BI-RIBBED	8"	X		150 feet	56 lbs.
	12"	X		150 feet	117 lbs.
	16"	X		150 feet	207 lbs.
	16"	X		100 feet	135 lbs.
SHEET	48" x 0.040"	X		50 yards	150 lbs.
	48" x 0.080"	X		40 yards	240 lbs.
	48" x 0.120"	X		30 yards	280 lbs.
	48" x 0.160"	X		20 yards	240 lbs.

LOW TEMP -30°F to +150°F					
FLAT	6" x 0.060"	X	X	400 feet	75 lbs.
	8" x 0.080"	X	X	300 feet	100 lbs.
	12" x 0.120"	X	X	200 feet	150 lbs.
	16" x 0.160"	X		150 feet	200 lbs.
BI-RIBBED	8"	X		150 feet	56 lbs.
	12"	X		150 feet	117 lbs.
	16"	X		150 feet	202 lbs.

EXTRA LOW TEMP -60°F to +120°F					
FLAT	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.120"	X		200 feet	150 lbs.

WELD SCREEN 0°F to +150°F					
FLAT	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.120"		X	200 feet	150 lbs.
	16" x 0.160"		X	150 feet	200 lbs.
SHEET	48" x 0.080"	X		40 yards	240 lbs.

ANTI-STATIC 0°F to +150°F					
FLAT	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.120"	X		200 feet	150 lbs.
SHEET	48" x 0.040"	X		50 yards	150 lbs.

SAFETY SCREEN 0°F to +150°F					
ORANGE FLAT	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.120"	X		200 feet	150 lbs.
	16" x 0.160"	X		150 feet	200 lbs.
RED FLAT	8" x 0.080"	X		300 feet	100 lbs.
	12" x 0.120"	X		200 feet	150 lbs.
ORANGE BI-RIBBED	12"	X		150 feet	117 lbs.

BLACK OPAQUE 0°F to +150°F					
FLAT	8" x 0.080"	X		300 feet	100 lbs.

Distributed by:

We reserve the right to change specifications without notice.

Products in this catalog are covered by U.S. Patent No. 4,776,382. Other Patents Pending.

Litho in USA

Flexon, Inc. 5/97