

# **FLEXON SERIES 600 RIGID DOCK SHELTER**



*"Control Your Environment"*



The Flexon Series 600 Rigid Frame Dock Shelter provides excellent weather protection for a wide range of truck and building variations. Trailers penetrate the vertical side curtains and the horizontal header curtain to seal the sides and top while permitting unobstructed accessibility to the interior. Recommended minimum trailer penetration is 14" based on the trailer size and style most commonly serviced. In most applications standard over the road trailers, straight trucks, and trucks with lift gates or extended rear bumpers can easily be sealed for safety and environmental control during loading and unloading. Rigid Shelters are a good solution for any size door opening up to 12'0" X 12'0".

## **SERIES 600 STANDARD FEATURES:**

- \* Several face curtain materials for light, medium and heavy-duty applications: 22oz and 40oz Vinyl; Bulldog high tear Vinyl; 40oz Hypalon and our exclusive Flexilon D-10.
- \* Standard color black.
- \* Flexible fiberglass stays are inserted into pockets and sewn into the side and head curtains to maintain positive contact on the top and sides of the trailer body.
- \* Side and header curtains are securely fastened to the frames and trimmed with aluminum angles.
- \* Wear Pleats on the corners of the header curtain provide extra wear resistance in critical wear areas.
- \* Foam-filled cushions secured to the bottom of the side frames provide a draft seal and are easily replaceable.
- \* Side Frames 2" X 4" pressure treated lumber covered with translucent white vinyl to allow light through.
- \* Head Frame 2" X 6" pressure treated lumber cover with translucent fiberglass to allow light through and support snow loads. Header raked 2" each side from center for drainage.
- \* Steel protective bumpers below each side frame. 6" C-Channel horizontal and diagonal brace with 8" C-Channel face. These bumpers project 6" beyond the side frames and protect them from damage from accidental truck contact.
- \* High visibility yellow guide stripes on the bottom of each side curtain.
- \* Wear areas sewn to the bottom of each side curtain providing additional wear resistance in critical areas.
- \* Shelter projection from building minimum 18" (based on 4" dock bumpers).
- \* Warranty: One year materials and workmanship.

## **OPTIONAL FEATURES:**

- \* Projections available in: 24", 30", 36", 42" or 48" (Over 48" Consult Factory).
- \* Translucent fiberglass covering on side frames.
- \* Tapered Projections: For inclined or declined approaches. (Consult Factory for Assistance).
- \* False Headers for door openings greater than 12'0" high on a 48" high dock.
- \* Common Member Side Frames when clearances between dock doors is limited.
- \* Head Curtain Drop Flaps with rope pulley adjustment to accommodate lower height trucks.
- \* Steel Side & Head Frames.

**FLEXON, INC. TOLL FREE: 800-365-3667 FAX: 412-749-0410**  
**EMAIL: [sales@flexoninc.com](mailto:sales@flexoninc.com) WEBSITE: [www.flexoninc.com](http://www.flexoninc.com)**  
**"CELEBRATING 25 YEARS OF DOOR & DOCK DESIGN EXCELLENCE"**